

## Open (high-sided) wagon of regular construction with flat flooring and front or side discharge

The following modifications of wagon series of this category make part of Železničná spoločnosť Cargo Slovakia, a.s. rolling stock fleet:

- Es
- Eas
- Eaos
- Eanos
- Eamos

with 2 axles

with 4 axles

with 6 or more axles

a with 4 axles

aa with 6 or more axles

c with unloading traps placed in wagon flooring 1)

**k** with 2 axles

with 4 axles

with 6 or more axles

kk with 2 axles

with 4 axles

with 6 or more axles

I not fitted for side discharge

II without floor flap valves 2)

m with 2 axles

with 4 or more axles

mm with 4 or more axles 2)

n with 2 axles

with 4 axles

with 6 or more axles

not fitted for front discharge

**p** with braking post 2)

loading length  $\leq$  7,7 m 25 t  $\leq$  loading capacity < 30 t loading length  $\geq$  12 m 50 t  $\leq$  loading capacity  $\leq$  60 t loading length  $\geq$  12 m 60 t  $\leq$  Loading capacity  $\leq$  75 t

loading capacity < 20 t

loading capacity < 40 t

loading capacity < 50 t

20 t ≤ loading capacity < 25 t

40 t ≤ loading capacity < 50 t

50 t ≤ loading capacity < 60 t

loading length < 7,7 m loading length < 12 m loading length < 12 m

loading capacity > 30 t

loading capacity > 60 t

loading capacity > 75 t

<sup>1)</sup> This notion is valid only for open wagons with flat flooring, fitted with device enabling wagon usage either as wagon of regular construction with flat floor or for gravity discharge of some commodities (using floor unloading traps).

<sup>2)</sup> Valid only for wagons of 1520 mm track gauge.